



masteroil

masteroil Hytec e-lixiere SP 0W-30

This is a full synthetic lubricant based on carefully selected very high quality base oils. This oil is specifically formulated to meet both the BMW Longlife-12 FE and the Ford WSS M2C950-A specification. It is adapted to meet the requirements of the latest technology, highly engineered turbo engines requiring high performance and lower viscosity oils.

APPLICATIONS

This product is mandatory in the newest BMW and Ford gasoline and diesel engines. It provides a multi vehicle application through the ACEA C2 specification. Optimum formulation for today's cars with exceptional film strength preventing oil film breakdown and reducing friction providing fuel economy and reliability.

FEATURES

Total engine protection: performance in keeping the engine clean. Fuel economy: superior fuel economy and CO2 reduction.

Cold start: excellent fluidity at low temperature.

PERFORMANCE

ACEA	C2
API	SN Plus
API	SP
ILSAC	GF-5
ALFA ROMEO	.
BMW	LONGLIFE-12 FE
DAIMLER TRUCK	DTRF 15D100
FIAT	9.55535-DS1
FIAT	9.55535-GS1
FORD	WSS-M2C950-A
JAGUAR-LAND-ROVER	STJLR.03.5007
MB	227.61
MB	229.61
OPEL	OV 040 1547 - G30
VW	530 35

RECOMMENDATIONS

GENESIS
HONDA
HYUNDAI
JEEP
KIA
LANCIA
LEXUS
MASERATI
MINI
MITSUBISHI
ROLLS-ROYCE
SsangYong
SUBARU
SUZUKI
TOYOTA

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.843
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	48.3
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	9.8
Viscosity index	ASTM D2270		194
B.N. (HClO ₄ method)	ASTM D2896	mg KOH/g	9.4
Pour point	ASTM D6892	°C	-48
Flash Point COC	ASTM D92	°C	224

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

01_2024

masteroil.com
masteroil GmbH | Stockholmer Allee 30 b | D – 44269 Dortmund |
info@masteroil.com

