



masteroil

masteroil Hytec e-lixiere C6 0W-20

This is a full synthetic lubricant mandatory for the newest engines requiring ACEA C6. It is developed to prolong the life and maintain the efficiency of emission systems. It is also designed to provide outstanding engine cleanliness, wear protection and strong durability to keep your engine running like new.

APPLICATIONS

This product has been specifically developed to meet the challenging requirements of the latest C6 standard (can be used where ACEA C5 is recommended). A standard where protection against LSPI, offering fuel economy and CO2 reduction are important. Its also designed to meet the newest FORD WWS- M2C952-A1 specification which is needed for the recent FORD Ecoblue engines (diesel).

FEATURES

Fuel economy: superior fuel economy and CO2 reduction. Cold start: excellent fluidity at low temperature.

Aftertreatment protection: full aftertreatment device protection

PERFORMANCE

API
GM
MB
ACEA
ILSAC
API
JAGUAR-LAND
ROVER
ACEA
FORD
OPEL

Recommendations:

HYUNDAI
KIA
SUZUKI
MITSUBISHI
TOYOTA
SUBARU
JEEP
NISSAN
HONDA
GMC
LEXUS
LINCOLN
SCION
TATA
ROEWE
TIANJIN
PERODUA
MG

ACURA
CHRYSLER
DODGE
MAZDA
INFINITI
CHEVROLET

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	39.8
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	8.3
Viscosity index	ASTM D2270		191
B.N. (HClO ₄ method)	ASTM D2896	mg KOH/g	9.4
Pour point	ASTM D6892	°C	-45
Flash Point COC	ASTM D92	°C	234
Density at 15°C	ASTM D4052	g/ml	0.843

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

01_2024

masteroil.com
masteroil GmbH | Stockholmer Allee 30 b | D – 44269 Dortmund |
info@masteroil.com