



# masteroil ATF DCG

## Description

masteroil ATF DCG is an HC synthetic lubricant based on carefully selected, very high-grade base oils. It was specifically developed for the dual clutch transmissions (DCTs) used in today's cars and ensures that these transmissions run smoothly.

## Application

masteroil ATF DCG is mainly intended for VAG's direct shift gearboxes (DSGs), but can also be used for other 6-speed dual clutch transmissions such as Chrysler Powershift, Ford Powershift, Mitsubishi TC SST and Volvo Powershift or the 7-gear BMW Drivelogic. This product is not intended for VW dry clutches of the DSG type 0AM, 02M, 02Q und 02S.

Typical characteristic values Property	Method	Unit	Value
Density at 15°C	ASTM D4052	g/ml	0.849
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	38.0
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	7.5
Viscosity index	ASTM D2270	-	170
Flash point (COC)	ASTM D92	°C	198
Pour point	ASTM D6892	°C	-50
Brookfield viscosity at -40°C	ASTM D2983	mPa-S	11110

We reserve the right to change our products' general properties so that our customers can always benefit from the latest technical developments.

## Specifications

- API GL-4
- 83220306816 / 83220397244 / 83220440214 / 83222147477 / 83222148578 / 83222148579 / 83222167666 / 83222409710 / 83222433157 / 83225B3AC81 / DCTF-1 / DCTF-2 / DTF 1 / FFL-4 / MTF LT-3 / MTF LT-5
- Chery 730DHB / DHC 7DCT300 / 738DHA / 7DCT380 / 9009011085
- Chrysler 68044345EA
- DAIMLER TRUCK DTFR 13C130
- Ferrari TF DCT-F3
- Fiat 9.55550-DA11 / 9.55550-MZ2 / 9.55550-MZ6
- Ford F-DC / WSS-M2C200-D2 / WSS-M2C200-D3 / WSS-M2C200-E1 / WSS-M2C218-A1 / WSS-M2C936-A
- GM FFL-4 / DEXRON DCT
- GREAT WALL GW7DCT1 / GWM 7DCT450
- HONDA MTF III
- HYUNDAI 04300-2N110 WDHO-1
- KIA 04300-2N110 WDHO-1
- KUNLUN DCTF-7S
- MB 236.21 / 236.22 / 236.24 / 236.25 / 239.21 / 239.22 / SLS A0019898603
- MCLAREN FFL-4
- Mitsubishi Diamond Queen SSTF-1
- NISSAN 999MP-6TRT00P / DCT FLUID / GR6 / GT-R R35 / LV MTF-1 / R35 SPECIAL
- Porsche 000.043.20 / 000.043.207.29 / 000.043.207.30 / 000.043.305.63 / 999.917.080.00 / 999.917.080.01 / 999.917.546.00 / TF 0870 / 000.043.210.44 / 971.094.307.02A
- PSA 1618078480 / 9730 A8 / 9734 S2 / JWS 2271
- Renault 7711579456 / 7711785243 / BOT450 EDC 6-Speed / DC4 / DW5 / DW6
- SINOPEC DCTF-GS
- SUZUKI 99000-22B27-036
- Toyota JWS 2271 / LF / LV 75W MT / 0888581001
- Volvo 1161520-7 / 1161839 / BOT341 #1161838 / 2240415 / 32240419 / D1 / D2
- VW G 052 178 / G 052 182 / G 052 512 / G 052 513 / G 052 527 / G 052 529 / G 052 726 / G 052 798 / G 055 512 / G 055 529 / G 055 549 / G 060 726 / G 070 726 / TL 521 82 / G 052 171 / G 052 524 / G 055 524 / G009317



masteroil

### **Advantages**

Wear protection: Significantly extended transmission service life. Friction properties: Very quiet gear changes without vibrations.

Extended oil life: Excellent temperature and oxidation stability.

### **Notes**

masteroil ATF DCG is not suitable for use in stepped automatic transmissions or in CVTs (continuously variable transmissions).

### **This product is available in the following container sizes:**

- 1 litre
- 5 litres
- 30 litres
- 60 litres