



masteroil C-Tec Power Special Longlife III 0W-30 masteroil

Description

masteroil C-Tec Power Special Longlife III 0W-30 was specifically developed for modern car petrol and diesel engines with exhaust gas after-treatment (diesel particulate filter = DPF), turbocharging and extended maintenance intervals and is based on high-grade and carefully selected base oils. The optimised viscosity grade guarantees optimum wear protection, even at the lowest outside temperatures. This engine oil is a mid-SAPS oil that complies with the Euro IV and Euro V emission guidelines and protects the diesel particulate filter. This viscosity grade has been proven to achieve greater fuel savings than the 5W-30 grade.

Application

masteroil C-Tec Power Special Longlife III 0W-30 is downwards compatible. 504.00 and 507.00 supersede all previous VW specifications (502.00, 503.00, 503.01, 505.00, 506.00 and 506.01) for all Volkswagen AG vehicles (Volkswagen, Audi, Seat, Škoda) that have extended oil change intervals (30,000 km or 2 years) and that were built from 2007 onwards. Note: This oil is not recommended for V10 TDI and five-cylinder 2.5 TDI engines built before 2007 that specification 506.01 applies to. First-generation engines with pump injectors should use specification 505.01.

Typical characteristic values Property	Method	Unit	Value
Density at 15°C	ASTM D4052	g/ml	0.842
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	59.0
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	11.7
Viscosity index	ASTM D2270	–	197
Base number (HClO ₄ method)	ASTM D2896	mg KOH/g	8.3
Pour point	ASTM D6892	°C	-48
Colour	Visual		Brown

We reserve the right to change our products' general properties so that our customers can always benefit from the latest technical developments.

Releases

- VW 504 00 / 507 00
- BMW LONGLIFE-04
- MB-Freigabe 229.51

Specifications

- ACEA C2 / C3
- API SN
- Fiat 9.55535-DS1 / -GS1 / -S3
- MB 229.31
- Porsche C30

Advantages

After-treatment protection: All-round protection of the after-treatment system.

Comprehensive engine protection: Excellent cleanliness and engine life. Fuel

efficiency: Low fuel consumption and low CO₂ emissions.

This product is available in the following container sizes:

- 0.5 litres
- 5 litres
- 30 litres
- 60 litres
- 206 litres
- Loose items