



masteroil

## masteroil Hytec e-lixiere Multi 5W-40

This synthetic engine oil is developed to suit the needs of some of the highest performing petrol engines. Thanks to its highly durable formula, this lubricant offers improved fuel economy and complete engine protection within even the most demanding engine designs. It is suitable for hybrid cars when the OEM specifications are met.

### APPLICATIONS

This engine oil enhances the performance of several W12, V10 and V8 engines of several manufacturers. Its top quality properties are proven by the VW 511 00 and Porsche C40 specifications, which broadens the lubricant's applicability to a range of Audi, Bentley and Lamborghini cars.

### FEATURES

Fuel economy: low fuel consumption and CO2 emissions  
Aftertreatment protection: full aftertreatment device protection  
Total engine protection: outstanding engine cleanliness and durability

### SPECIFICATIONS:

VW	511 00
ACEA	C3-16
RENAULT	RN 0700
RENAULT	RN 0710
BMW	LONGLIFE-04
API	SN/CF
GM	dexos2™
PORSCHE	C40
MB	226.5
MB	229.31
MB	229.51
MB	229.52
ACEA	C3
FIAT	9.55535-GH2
FIAT	9.55535-S2
FORD	WSS-M2C917-A
VW	505 00
VW	505 01

### RECOMMENDATIONS::

HYUNDAI  
KIA  
SUZUKI  
MITSUBISHI

## TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.850
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	73.0
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	13.5
Viscosity index	ASTM D2270		191
B.N. (HClO <sub>4</sub> method)	ASTM D2896	mg KOH/g	7.8
Pour point	ASTM D6892	°C	-42
Sulfated Ash	ASTM D874	Mass %	0.79
Flash Point COC	ASTM D92	°C	222

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

