



masteroil

masteroil C-Tec Power Longlife IV 0W-20

Description

masteroil C-Tec Power Longlife IV 0W-20 is an HC synthetic lubricant that is suitable for the latest VW / Audi engines. The optimum coordination of these base oils and the additives developed specifically for this application is what gives this engine oil its outstanding performance level. The lubricant was developed to extend the life and maintain the efficiency of emission systems.

Application

masteroil C-Tec Power Longlife IV 0W-20 was specifically developed for the current Volkswagen standard VW 508 00 / 509 00 and is therefore recommended for the new 2.0 TFSI (140 kW) und 3.0 TDI CR (160 kW) engines. In addition, it is excellently suited to other vehicles requiring one of the viscosity grades 0W-20 mentioned in SAE. masteroil C-Tec Power Longlife IV 0W-20 guarantees lasting, maximum engine wear protection with optimised fuel savings and lasting engine cleanliness at the same time. masteroil C-Tec Power Longlife IV 0W-20 exceeds Volkswagen's stringent requirements in all prescribed engine tests.

Typical characteristic values Property	Method	Unit	Value
Density at 15°C	ASTM D4052	g/ml	0.835
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	40.2
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	8.2
Viscosity index	ASTM D2270	-	184
Base number (HClO ₄ method)	ASTM D2896	mgKOH/g	8.3
Pour point	ASTM D6892	°C	-51
Sulphated ash	ASTM D874	Mass %	0.79
Flash point (COC)	ASTM D92	°C	235
CCS viscosity at -35°C	ASTM D 5293	mPa-S	3500
Colour	Visual		Green

We reserve the right to change our products' general properties so that our customers can always benefit from the latest technical developments.

Releases

- VW 508 00 / 509 00
- Porsche C20

Specifications

- ACEA C5 / C6
- API SN Plus / SP
- Ford WSS-M2C956-A1
- ILSAC GF-6 A
- VW TL 52 577

Advantages

General engine protection: Keeps the engine powerful and clean.
Fuel consumption: Low fuel consumption and low CO₂ emissions. Cold start: Excellent flowability at low temperatures.

This product is available in the following container sizes:

- 0.5 litres
- 5 litres
- 30 litres
- 60 litres
- 206 litres
- Loose items

04_2024

masteroil GmbH | Stockholmer Allee 30b | D – 44269 Dortmund | info@masteroil.com masteroil.com

