



masteroil C-Tec Special V 0W-30

Description

This is an HC synthetic lubricant based on carefully selected, very high-grade base oils and specifically developed to meet the requirements placed on Volvo cars. It features improved lubrication properties and increased fuel efficiency. As a result, it consumes less fuel and extends the engine's life.

Application

This oil is recommended for the latest-generation Volvo Cars petrol and diesel models that are fitted with a five-cylinder engine.

Typical characteristic values Property	Method	Unit	Value
Density at 15°C	ASTM D4052	g/ml	0.844
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	53.2
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	10.0
Viscosity index	ASTM D2270	-	180
Base number (HClO ₄ method)	ASTM D2896	mg KOH/g	10.0
Pour point	ASTM D6892	°C	-45
Sulphated ash	ASTM D874	Mass %	1.09
Flash point (COC)	ASTM D92	°C	220
CCS viscosity at -35°C	ASTM D5293	mPa-S	6000

We reserve the right to change our products' general properties so that our customers can always benefit from the latest technical developments.

Releases

- Volvo VCC 95200377

Specifications

- ACEA A5/B5
- ACEA A7/B7
- API SN/CF
- BMW LONGLIFE-01 FE
- VW 503 00 / 506 00 / 506 01
- Renault RN 0700

Advantages

Wear protection: Considerably reduces wear.

Fuel savings: Ensures fuel savings and low CO₂ emissions

This product is available in the following container sizes:

- 0.5 litres
- 5 litres
- 30 litres
- 60 litres
- 206 litres

