



masteroil

Technical Data Sheet

masteroil Engine Oil Circuit Flush

Art.-No.: 0055102350250

Technical Data

Appearance:	Bright clear yellowish liquid
density (15 °C):	0,91-0,92 g/cm ³
viscosity (at 20°C):	25 mm ² /s
(at 25°C):	12 mm ² /s
(at 40°C):	8 mm ² /s
(at 100°C):	3 mm ² /s
flash point:	140 °C
pour point:	-57°C

Ingredients:

Combination of highly concentrated detergents, stabilisers and emulsifiers in aromatic solvent.

Product description:

Professional additive for cleaning of engine oil sump before changing the engine oil. The additive is developed for professional use only.

Field of Application:

This product is a top treat to be poured into the engine prior to a fluid change. Add the content of the can (250 ml) into the engine oil sump and run the vehicle for 5 – 15 minutes and then flush per the normal procedures.

Benefits:

- ✓ contains a special formulation that helps clean and prepare an engine for a new fluid.
- ✓ Works with all engine oils
- ✓ dilution of old engine oil for a better removing of the residues
- ✓ dissolving of the deterioration products from the surfaces
- ✓ avoids the sedimentation of gums and particulate matter
- ✓ neutralization of the acids
- ✓ protection against corrosion



masteroil

Product advantages:

- ✓ Fast and reliable cleaning
- ✓ Ensures an optimal supply of oil, protects the engine from damage
- ✓ Does not damage gaskets or engine components
- ✓ Use in conjunction with an oil change
- ✓ Suitable for all engine oils

Application:

Use the oil filler neck to add the additive to the engine oil at operating temperature prior to an oil change. Then let the engine idle for 5–15 minutes. After this, change the oil and the oil filter. One bottle (250 ml) is enough for 4 litres of engine oil.

Dosage:

Recommended dosage rate 1:16, 250ml for 4 litres engine oil

Supply form:

The additive is available in a 250ml can.

Storage:

Store in a dry place at room temperature, temporarily higher temperatures are unproblematic. Opened containers should be resealed correctly. Avoid storage in direct sunlight. The shelf life of the products is 24 months minimum. Empty containers should be properly disposed.

Safety Considerations:

For detailed handling precautions see masteroil safety data sheet No. 2354

User instructions:

The information and our technical advice are given in good faith according to our best knowledge but without warranty, and this also applies where proprietary rights of third parties are involved.