



masteroil C-Tec Power 10W-40

Description

masteroil C-Tec Power 10W-40 is an HC synthetic lubricant based on carefully selected, highly refined base oils. This oil is an advanced engine oil specifically designed to meet the requirements of ACEA A3/B4-08 and the Euro 4 standard. Among other things, it is characterised by low ash formation and high ageing resistance.

Application

masteroil C-Tec Power 10W-40 is particularly suitable for vehicles with petrol and diesel engines both with and without turbocharging. It is used for vehicles that do not have extended maintenance intervals. The modern concept of masteroil C-Tec Power 10W-40 enables a wide range of applications and ensures safe operation under all operating conditions.

Typical characteristic values Property	Method	Unit	Value
Density at 15°C	ASTM D4052	g/ml	0.866
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	91.0
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	13.8
Viscosity index	ASTM D2270	–	155
Base number (HClO ₄ method)	ASTM D2896	mg KOH/g	8.3
Pour point	ASTM D6892	°C	-39
Flash point (COC)	ASTM D92	°C	220
CCS viscosity at -25°C	ASTM D5293	mPa·s	6700
Sulphated ash (COC)	ASTM D874	Mass %	1.0

We reserve the right to change our products' general properties so that our customers can always benefit from the latest technical developments.

Specifications

- ACEA A3/B3-16; A3/B4
- API SN/CF
- Fiat 9.55535-G2 / D2
- MB 229.1
- Renault RN 0700 / RN 0710
- VW 501 01 / 505 00

Advantages

Comprehensive engine protection: Excellent cleanliness and engine life.

This product is available in the following container sizes:

- 0.5 litres
- 5 litres
- 60 litres
- 206 litres
- Loose items