



masteroil

# masteroil C-Tec Power Multi 5W-40

## Description

masteroil C-Tec Power Multi 5W-40 is a high-performance engine oil based on HC synthetic oil and special additives with a wide range of applications. Specifically developed for modern cars with / without extended maintenance intervals and with exhaust after-treatment systems.

## Application

masteroil C-Tec Power Multi 5W-40 is a mid-SAPS oil (with medium sulphated ash, phosphorus and sulphur content), meets Euro 4 and Euro 5 standards and reliably protects after-treatment systems and diesel particulate filters. This oil is especially recommended for the lubrication of all TDI engines with injection pump and common rail turbo diesel engines.

Typical characteristic values Property	Method	Unit	Value
Density at 15°C	ASTM D4052	g/ml	0.851
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	84.7
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	13.9
Viscosity index	ASTM D2270	–	170
Base number (HClO <sub>4</sub> method)	ASTM D2896	mg KOH/g	7.5
Pour point	ASTM D6892	°C	-39
CCS viscosity at -30°C	ASTM D5293	mPa-S	5970
Sulphated ash	ASTM D874	Mass %	0.8
Flash point (COC)	ASTM D92	°C	235

We reserve the right to change our products' general properties so that our customers can always benefit from the latest technical developments.

## Releases

- MB release 229.51
- VW 505 01 / 505 00

## Specifications

- ACEA C3
- API SN / CF
- BMW Longlife-04
- Fiat 9.55535-GH2 / – S2
- Ford WSS-M2C917-A
- GM dexos2™
- MB 226.5 / 226.31
- Porsche A40
- Renault RN 0700 / 0710

## Advantages

After-treatment protection: All-round protection of the after-treatment system.  
Comprehensive engine protection: Excellent cleanliness and engine life. Fuel efficiency: Low fuel consumption and low CO<sub>2</sub> emissions.

## This product is available in the following container sizes:

- 0.5 litres
- 5 litres
- 30 litres
- 60 litres
- 206 litres
- Loose items

