



masteroil C-Tec Special C4 5W-30

Description

masteroil C-Tec Special C4 5W-30 is an HC synthetic lubricant based on carefully selected, very high-grade base oils and was specifically developed to protect the after-treatment system of Renault engines.

Application

masteroil C-Tec Special C4 5W-30 protects the particulate filter due to a reduced sulphated ash content and, at the same time, offers fuel savings potential due to its smooth running characteristics. It is used according to the manufacturer's specifications in vehicles with petrol and diesel engines both with and without a turbocharger and diesel particulate filter.

Typical characteristic values Property	Method	Unit	Value
Density at 15°C	ASTM D4052	g/ml	0.852
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	67.1
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	11.8
Viscosity index	ASTM D2270	–	173
Base number (HClO ₄ method)	ASTM D2896	mg KOH/g	6.4
Pour point	ASTM D6892	°C	-39
CCS viscosity at -30°C	ASTM D5293	mPa·s	5800
Sulphated ash	ASTM D874	Mass %	0.5
Flash point (COC)	ASTM D92	°C	220

We reserve the right to change our products' general properties so that our customers can always benefit from the latest technical developments.

Releases

- MB release 229.51

Specifications

- ACEA C3; C4
- Fiat 9.55535-S4
- MB 226.51 / 229.31
- Renault RN 0720

In addition, this product is recommended when the following filling instructions are required

- Nissan
- Suzuki

Advantages

After-treatment protection: All-round protection of the after-treatment system.

Comprehensive engine protection: Excellent cleanliness and engine life. Fuel

efficiency: Low fuel consumption and low CO₂ emissions.

This product is available in the following container sizes:

- 0.5 litres
- 5 litres
- 30 litres
- Loose items