masteroil

masteroil MULTI ATF FE

Description

This transmission fluid is an HC synthetic, heavy-duty ultra-high-performance transmission fluid. It was specifically designed for significantly extended change intervals. The oil consists of premium-grade synthetic base oils and is suitable for automatic truck transmissions and HGV and bus transmission systems.

Application

This transmission fluid is designed for long oil change intervals in automatic transmissions in HGVs and buses, as well as for transmissions in commercial vehicles and other heavy-duty applications.

Typical characteristic values Property	Method	Unit	Value
Density at 15°C	ASTM D4052	g/ml	0.844
Kinematic viscosity at 40°C	ASTM D445	mm²/s	38.7
Kinematic viscosity at 100°C	ASTM D445	mm²/s	7.3
Viscosity index	ASTM D2270	-	158
Pour point	ASTM D6892	°C	-54
Brookfield viscosity at -40°C	ASTM D2983	mPa-S	15400
Colour	VISUAL		RED

We reserve the right to change our products' general properties so that our customers can always benefit from the latest technical developments.

Specifications

- V VOITH H55.6335xx
- Aisin Warner AW-1 / JWS 3324/ AW-2
- · Allison C4;
- BMW 83 22 0 397 114 / 83 22 2 305 397 / 83 22 9 407 858 / 83222152426 / 83222167718 / 83222413477 / ATF 3 / ATF 6 / ATF 7 / L 12108 / M-1375.4 / 000 043 306 24 / 958 300 540 00
- · Chrysler 68157995AA
- Fiat 9.55550-AV2 / AV5
- Ford MERCON LV / MERCON SP / WSS-M2C195-A / WSS-M2C924-A / WSS-M2C938-AGM Dexron HP / Dexron VI
- GM DEXRON HP / DEXRON VI
- Honda DW1 / DPSF / DPSF2
- Hyundai NWS-9638 T5 / SPH-IV / SP-IV
- · Isuzu WSI
- Jaguar 02JDE26444
- Land Rover LR023288
- Mazda FZ
- MB 236.12 / 236.14 / 236.41
- Mitsubishi ATF J3 / Diaqueen ATF PA
- · Nissan Matic-S
- PSA 1635056080
- Tesla ATF9/EDF2
- · Toyota Auto Fluid WS
- VOLVO 31492172 / 31492173
 - VW G 053 001 / G 055 005 / G 055 162 / G 055 540 / G 060 162

Advantages

Very smooth shifting behaviour, no vibrations: Very quiet gear changes without vibrations Significantly extended transmission service life: Significantly extended transmission service life Excellent temperature and oxidation stability: Excellent thermal and oxidation stability

This product is available in the following container sizes:

- 1 litre
- 5 litres
- 30 litres
- 60 litres

masteroil.com masteroil GmbH | Stockholmer Allee 30 b | D – 44269 Dortmund| info@masteroil.com

01_2025