



masteroil

Technical Data Sheet

masteroil Benzin System-Langzeitschutz

Art.-No.: 0055201100255

Technical Data

Appearance:	clear yellow-brownish liquid
density (15 °C):	0,82-0,83 g/cm ³
viscosity (at 20°C):	3,85 mm ² /s
Flash point:	> 55 °C

Ingredients:

High concentrated combination of friction modifiers, corrossions inhibitors and detergents in mineral oil.

Product description:

The masteroil Benzin System-Langzeitschutz Protection is designed to combat dirt deposits in the fuel injection systems and valves of modern car engines.

Field of Application:

Designed for regular application.

Add to an almost empty tank and allow the engine to run under load for approx. 15 minutes. After cleaning procedure fill up the tank normally. Repeat the application after 3000-5000 km.

Benefits:

Deposits on the valves and on the surfaces of the injection jets reduce the fuel flow and lead to decreasing of injection performance. As a result of these deposits increased fuel consumption, higher level of exhaust emissions, as well knocking engine running. The fuel-air mixture cannot form properly. Engine performance suffers accordingly. The longer an engine runs on standard-quality fuel (i.e. without special additives) the greater is the reduction in fuel flow due to deposit formation. The high concentrated masteroil Benzin System-Langzeitschutz removes deposits from valves, from the injection jets and other fuel system components.

Product advantages:

- ✓ Preventive protection for the petrol fuel system



masteroil

- ✓ Prevents deposits, coking, lubricating films etc.
- ✓ Suitable for turbo engines and catalytic converters
- ✓ Ideal for maintaining the value of your petrol vehicle in the longer term
- ✓ Permanent preservation of engine performance if used regularly
- ✓ Suitable for all gasoline engines and fuel qualities (E5, E10 or E85)

Application:

Add the entire contents of the bottle to an almost empty tank (fuel reserve) and then spend about 15 minutes driving the vehicle. After this, refuel the vehicle. The process should be repeated every 3,000–5,000 km.

Dosage:

Recommended dosage rate 1:15 (66667 mg/kg)

Supply form:

The additive is available in a 250ml can with a pouring spout.

Storage:

Store in a dry place at room temperature, temporarily higher temperatures are unproblematic. Opened containers should be resealed correctly. Avoid storage in direct sunlight. The shelf life of the products is 24 months minimum. Empty containers should be properly disposed.

Safety Considerations:

For detailed handling precautions see masteroil safety data sheet No. 1122

User instructions:

The information and our technical advice are given in good faith according to our best knowledge but without warranty, and this also applies where proprietary rights of third parties are involved.