



masteroil

masteroil C-Tec Special AA 5W-20

Description

Thanks to its low viscosity and excellent flowability, this HC synthetic oil significantly reduces wear and guarantees fuel savings and lower CO₂ emissions. The optimised additive package reduces the formation of soot and deposits and keeps the engine clean. It is suitable for hybrid vehicles if the OEM specifications are met.

Application

This product was specifically developed in view of the challenging requirements set out in the current ILSAC GF-6 A standard, for which high fuel efficiency and low CO₂ emissions are tremendously important. It provides the performance required to meet the demands of the state-of-the-art petrol cars from US and Asian manufacturers.

Typical characteristic values Property	Method	Unit	Value
Density at 15°C	ASTM D4052	g/ml	0.8486
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	45.1
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	8.48
Viscosity index	ASTM D2270	-	168
Base number (HClO ₄ method)	ASTM D2896	mg KOH/g	8.5
Pour point	ASTM D6892	°C	-39
Flash point (COC)	ASTM D92	°C	230

We reserve the right to change our products' general properties so that our customers can always benefit from the latest technical developments.

Specifications

- API SN Plus; SN/RC; SP; SP/RC
- Chrysler MS 6395
- Fiat 9.55535-CR1
- Ford WSS-M2C945-A
- Ford WSS-M2C946-A
- Ford WSS-M2C947-A
- Ford WSS-M2C960-A1
- Ford WSS-M2C962-A
- GM dexos1™ Gen 3
- ILSAC GF-5
- ILSAC GF-6 A

In addition, this product is recommended when the following filling instructions are required

- Buick
- Chevrolet
- Chrysler
- Dodge
- Fiat
- Ford
- Hyundai
- Jeep
- Kia
- Lancia
- Lexus
- Lincoln
- Mazda
- Mitsubishi
- Scion
- Ssang Yong
- Tianjin
- Toyota

Advantages

Wear protection: Considerably reduces wear.

Cleanliness: Additive package reduces soot and deposits.

Fuel savings: Ensures fuel savings and low CO₂ emissions

This product is available in the following container sizes:

- 0.5 litres
- 5 litres
- 30 litres
- 60 litres
- 206 litres