



masteroil

masteroil Regular Truck 10W-40

Description

masteroil Regular Truck 10W-40 is an HC synthetic lubricant based on carefully selected, highly refined base oils. This oil was developed to meet the latest specifications laid down by European and American manufacturers of heavy-duty diesel engines. It offers excellent protection against deposits in the oil lines and in turbo engines, not to mention improved protection against camshaft wear.

Application

Suitable for low-emission engines according to the Euro II and Euro III standards. This oil cannot be used for Euro IV engines with particulate filters. The oil enables very long oil change intervals.

Typical characteristic values Property	Method	Unit	Value
Density at 15°C	ASTM D4052	g/ml	0.863
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	88.4
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	13.8
Viscosity index	ASTM D2270	–	160
Base number (HClO ₄ method)	ASTM D 2896	mg KOH/g	10.1
Pour point	ASTM D6892	°C	-39
CCS viscosity at -39°C	ASTM D5293	mPa-S	5500
Flash point (COC)	ASTM D92	°C	227
Sulphated ash	ASTM D874	Mass %	1.49

We reserve the right to change our products' general properties so that our customers can always benefit from the latest technical developments.

Releases

- Mack EO-N
- MB-Freigabe 228.3
- Renault RLD-2
- Volvo VDS-3

Specifications

- ACEA A3/B4; E7
- API CF-4 / CG-4 / CH-4 / CI-4/SL
- Allison C4
- Caterpillar ECF-1a / ECF-2/ TO-2
- Cummins CES 20076 / -77 / -78
- DAIMLER TRUCK DTFR 15B110
- Detroit Diesel 93K215
- Deutz DQC III-10 / -18
- GLOBAL DHD-1
- IVECO 18-1804 Classe T2 E7
- JASO DH-1
- MACK EO-M PLUS / EO-N
- MAN M 3275-1
- MB 229.1
- MTU Oil Category 1 / 2
- Renault RLD / RLD-2
- Volvo VDS-3

Advantages

Comprehensive engine protection: Excellent cleanliness and engine life. Cold start: Very good flowability at low temperatures.

This product is available in the following container sizes:

- 5 litres
- 30 litres
- 60 litres
- 206 litres
- Loose items

04_2024

masteroil.com
masteroil GmbH | Stockholmer Allee 30 b | D – 44269 Dortmund | info@masteroil.com