



masteroil

masteroil C-Tec Special F x B FE 0W-30

This is a full synthetic lubricant based on carefully selected very high quality base oils. This oil is specifically formulated to meet both the BMW Longlife-12 FE and the Ford WSS M2C950-A specification. It is adapted to meet the requirements of the latest technology, highly engineered turbo engines requiring high performance and lower viscosity oils.

Applications

This product is mandatory in the newest BMW and Ford gasoline and diesel engines. It provides a multi vehicle application through the ACEA C2 specification. Optimum formulation for today's cars with exceptional film strength preventing oil film breakdown and reducing friction providing fuel economy and reliability.

Typical Characteristics:

Test	Method	Unit	Average result
Density at 15°C	ASTM D4052	g/ml	0.843
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	48.3
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	9.8
Viscosity index	ASTM D2270		194
B.N. (HClO4 method)	ASTM D2896	mg KOH/g	9.4
Pour point	ASTM D6892	°C	-48
Flash Point COC	ASTM D92	°C	224
Density at 15°C	ASTM D4052	g/ml	0.843

Wir behalten uns das Recht vor, die allgemeinen Eigenschaften unserer Produkte zu ändern, damit unsere Kunden jederzeit von den neusten technischen Entwicklungen profitieren können.

Releases:

- MB-Freigabe 229.51
- BMW Longlife-12 FE
- Daimler Truck DTFR 15D100
- MB-Freigabe 229.61

Specifications:

- ACEA C2
- API SN Plus
- API SP
- Alfa Romeo
- Fiat 9.55536-DS1 / - GS1
- Ford WSS-M2C950-A
- Genesis
- Honda
- Hyundai
- ILSAC GF-5
- Jaguar-Land Rover STJLR.03.5007
- Jeep
- Kia
- Lancia
- Lexus
- Maserati
- Mini
- Mitsubishi
- Opel OV 040 1547 – G30
- Rolls-Royce
- Ssang Yong
- Subaru
- Suzuki
- Toyota



Features:

Total engine protection: performance in keeping the engine clean. Fuel economy: superior fuel economy and CO2 reduction.

Cold start: excellent fluidity at low temperature.

Available in :

- 0,5 Liter
- 5 Liter
- 30 Liter
- 60 Liter
- 206 Liter
- bulk