



masteroil

## Technical Data Sheet

### masteroil Oil Stop-Leak

Art.-No.: 0055102200250

#### Technical Data

Appearance:	Clear yellow-brownish liquid
density (g/cm <sup>3</sup> ):	0,92 (at 15°C)
viscosity (at 20°C):	332 mm <sup>2</sup> /s
(at 40°C):	129 mm <sup>2</sup> /s
(at 100°C):	25 mm <sup>2</sup> /s
flash point (°C):	121
pour point (°C):	- 30
viscosity index:	(246.7)

#### Ingredients:

Combination of viscosity index improver (polyalkyl methacrylate, PAMA) and lubricity improver in a highly refined high-viscosity mineral oil. Shows Pour-Point Depressant properties, for multi-grade engine oils.

#### Product description:

The masteroil Oil Stop-Leak Additive provides effective thickening and VI improvement for a good shear stability level. Effectively controls the paraffine cristallisation and enables blending to achieve engine oils with superior low-temperature viscosities and pour points. The liquid form provides an easy handling.

#### Field of Application:

Masteroil Oil Stop-Leak is designed for a single application (in emergency case – after every oil change). Applicable in all commercial diesel and gasoline engines and compatible with all mineral and synthetic motor oils.

#### Benefits:

Engine seals become brittle and begin to leak in the course of time. The Additive restores the elasticity of all engine seals and effectively stops oil leaks. Attention: not for automatic transmission!



masteroil

**Product advantages:**

- ✓ Restores elasticity to seals
- ✓ Reliably seals oil leaks
- ✓ Reduces the engine's oil consumption
- ✓ Provides protection against engine damage
- ✓ Protects the environment
- ✓ Suitable for all engine oils

**Application:**

Use the oil filler neck to add the additive when the engine is at operating temperature. One bottle (250 ml) is enough for 4 litres of engine oil. masteroil Oil Stop-Leak is designed for single use (or after every oil change if needed) and is suitable for all petrol and diesel engines, as well as all mineral and synthetic oils.

**Dosage:**

Recommended dosage rate 1:16 (250 ml for 4 l engine oil sump).

**Supply form:**

The additive is available in a 250ml can with a pouring spout.

**Storage:**

Store in a dry place at room temperature, temporarily higher temperatures are unproblematic. Opened containers should be resealed correctly. Avoid storage in direct sunlight. The shelf life of the products is 24 months minimum. Empty containers should be properly disposed.

**Safety Considerations:**

For detailed handling precautions see masteroil safety data sheet No. 2206

**User instructions:**

The information and our technical advice are given in good faith according to our best knowledge but without warranty, and this also applies where proprietary rights of third parties are involved.