

Trade name: masteroil Diesel Extra-Power**Product no.:** 1606**Current version :** 1.0.2, issued: 21.04.2022**Replaced version:** 1.0.1, issued: 17.01.2022**Region:** IE**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifier****Trade name****masteroil Diesel Extra-Power****UFI:****NCV5-C0QP-E006-2F86****1.2 Relevant identified uses of the substance or mixture and uses advised against****Relevant identified uses of the substance or mixture**

Additive for mineral oil products

Uses advised against

No data available.

1.3 Details of the supplier of the safety data sheet**Address**Masteroil GmbH
Stockholmer Allee 30 b
44269 Dortmund

Telephone no. 0231 444 247 64

e-mail info@masteroil.com

Advice on Safety Data Sheet

sdb_info@umco.de

1.4 Emergency telephone number

+353 1 809 2166 (National Poisons Information Centre)

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture****Classification in accordance with Regulation (EC) No 1272/2008 (CLP)**

Aquatic Chronic 3; H412

Asp. Tox. 1; H304

Classification information

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

2.2 Label elements**Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)****Hazard pictograms**

GHS08

Signal word

Danger

Hazardous component(s) to be indicated on label:

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, aromatics (2-30 %)

**Trade name:** masteroil Diesel Extra-Power**Product no.:** 1606**Current version :** 1.0.2, issued: 21.04.2022**Replaced version:** 1.0.1, issued: 17.01.2022**Region:** IE**Hazard statement(s)**

H304 May be fatal if swallowed and enters airways.
 H412 Harmful to aquatic life with long lasting effects.

Hazard statements (EU)

EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statement(s)

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.
 P331 Do NOT induce vomiting.

UFI:

NCV5-C0QP-E006-2F86

2.3 Other hazards

PBT assessment
 No data available.

vPvB assessment
 No data available.

SECTION 3: Composition/information on ingredients**3.1 Substances**

Not applicable. The product is not a substance.

3.2 Mixtures**Hazardous ingredients**

No	Substance name	Additional information	
	CAS / EC / Index / REACH no	Classification (EC) 1272/2008 (CLP)	Concentration %
1	Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)		
	- 925-653-7 - 01-2119458869-15	EUH066 Asp. Tox. 1; H304 Aquatic Chronic 3; H412	>= 25,00 - < 50,00 wt%
2	Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, aromatics (2-30 %)		
	- 920-360-0 - 01-2119448343-41	Asp. Tox. 1; H304 EUH066	>= 25,00 - < 50,00 wt%
3	2-ethylhexyl nitrate		
	27247-96-7 248-363-6 - 01-2119539586-27	Acute Tox. 4; H302 Acute Tox. 4; H312 Acute Tox. 4; H332 Aquatic Chronic 2; H411 EUH044 EUH066	>= 10,00 - < 20,00 wt%
4	hydrocarbons, C10, aromatics, <1% naphthalene		
	- 918-811-1 - 01-2119463583-34	Aquatic Chronic 2; H411 Asp. Tox. 1; H304 EUH066 STOT SE 3; H336	< 2,50 wt%

Full Text for all H-phrases and EUH-phrases: pls. see section 16

SECTION 4: First aid measures**4.1 Description of first aid measures****General information**

Trade name: masteroil Diesel Extra-Power**Product no.:** 1606**Current version :** 1.0.2, issued: 21.04.2022**Replaced version:** 1.0.1, issued: 17.01.2022**Region:** IE

Remove contaminated clothing and shoes immediately, and launder thoroughly before reusing. If the patient is likely to become unconscious, place and transport in stable sideways position. In case of persisting adverse effects, consult a physician.

After inhalation

Remove affected person from the immediate area. Ensure supply of fresh air.

After skin contact

In case of contact with skin wash off immediately with soap and water.

After eye contact

Remove contact lenses. Rinse eye thoroughly under running water keeping eyelids wide open and protecting the unaffected eye (at least 10 to 15 minutes). Seek medical assistance.

After ingestion

Do not induce vomiting - aspiration hazard. Rinse the mouth thoroughly with water. Never give anything by mouth to an unconscious person. If individual is drowsy or unconscious, place in recovery position (on left side, with head down).

4.2 Most important symptoms and effects, both acute and delayed

No data available.

4.3 Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5: Firefighting measures**5.1 Extinguishing media****Suitable extinguishing media**

Water spray jet; Foam; Carbon dioxide; Extinguishing powder

Unsuitable extinguishing media

High power water jet

5.2 Special hazards arising from the substance or mixture

In the event of fire, the following can be released: Carbon dioxide (CO₂); Carbon dioxide (CO₂); Vapours are heavier than air and may spread near ground to sources of ignition. May travel considerable distance to source of ignition and flash back.

5.3 Advice for firefighters

Use self-contained breathing apparatus. Wear protective clothing. Cool endangered containers with water spray jet. Do not allow run-off from fire fighting to enter drains or water courses.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures****For non-emergency personnel**

Refer to protective measures listed in sections 7 and 8. Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. Keep away from ignition sources.

For emergency responders

No data available. Personal protective equipment (PPE) - see Section 8.

6.2 Environmental precautions

Do not discharge into the drains/surface waters/groundwater. Do not discharge into the subsoil/soil.

6.3 Methods and material for containment and cleaning up

Take up with absorbent material (e.g., sand, kieselguhr, universal binder). When collected, handle material as described under the section heading "Disposal considerations".

6.4 Reference to other sections

No data available.

SECTION 7: Handling and storage

**Trade name:** masteroil Diesel Extra-Power**Product no.:** 1606**Current version :** 1.0.2, issued: 21.04.2022**Replaced version:** 1.0.1, issued: 17.01.2022**Region:** IE**7.1 Precautions for safe handling****Advice on safe handling**

Provide good ventilation at the work area (local exhaust ventilation, if necessary). If workplace exposure limits are exceeded, respiratory protection approved for this particular job must be worn. Risks inherent to handling the product must be minimised by applying the appropriate protective and preventive measures. Working processes should - so far as possible, according to the state of the art - be designed to rule out bodily contact or the release of hazardous substances.

General protective and hygiene measures

Do not eat, drink or smoke during work time. Keep away from foodstuffs and beverages. Avoid contact with eyes and skin. Remove soiled or soaked clothing immediately. Wash hands before breaks and after work.

Advice on protection against fire and explosion

Keep away from sources of heat and ignition.

7.2 Conditions for safe storage, including any incompatibilities**Technical measures and storage conditions**

Keep container tightly closed in a cool, well-ventilated place.

Recommended storage temperature

Value < 50 °C

Requirements for storage rooms and vessels

Containers which are opened must be carefully closed and kept upright to prevent leakage. Keep only in the original container. Protect from heat and direct sunlight.

Incompatible products

Do not store together with: Acids; Alkalies; oxidizing agents

7.3 Specific end use(s)

No data available.

SECTION 8: Exposure controls/personal protection**8.1 Control parameters****DNEL, DMEL and PNEC values****DNEL values (worker)**

No	Substance name			CAS / EC no
	Route of exposure	Exposure time	Effect	Value
1	2-ethylhexyl nitrate			27247-96-7 248-363-6
	dermal	Long term (chronic)	systemic	1 mg/kg/day
	dermal	Long term (chronic)	local	44 µg/cm ²
	inhalative	Long term (chronic)	systemic	0.35 mg/m ³
2	hydrocarbons, C10, aromatics, <1% naphthalene			- 918-811-1
	dermal	Long term (chronic)	systemic	12,5 mg/kg/day
	inhalative	Long term (chronic)	systemic	151 mg/m ³

DNEL value (consumer)

No	Substance name			CAS / EC no
	Route of exposure	Exposure time	Effect	Value
1	2-ethylhexyl nitrate			27247-96-7 248-363-6
	oral	Long term (chronic)	systemic	25 µg/kg/day
	dermal	Long term (chronic)	systemic	0.52 mg/kg/day
	dermal	Long term (chronic)	local	22 µg/cm ²
	inhalative	Long term (chronic)	systemic	87 µg/m ³
2	hydrocarbons, C10, aromatics, <1% naphthalene			- 918-811-1

**Trade name:** masteroil Diesel Extra-Power**Product no.:** 1606**Current version :** 1.0.2, issued: 21.04.2022**Replaced version:** 1.0.1, issued: 17.01.2022**Region:** IE

	oral	Long term (chronic)	systemic	7,5	mg/kg/day
	dermal	Long term (chronic)	systemic	7,5	mg/kg/day
	inhalative	Long term (chronic)	systemic	32	mg/m ³

PNEC values

No	Substance name	CAS / EC no	
	ecological compartment	Type	Value
1	2-ethylhexyl nitrate		27247-96-7 248-363-6
	water	fresh water	0,8 µg/L
	water	marine water	0,08 µg/L
	water	fresh water sediment	0,00074 mg/kg dry weight
	water	marine water sediment	0,00074 mg/kg dry weight
	soil	-	0,000191 mg/kg dry weight
	sewage treatment plant	-	10 mg/L

8.2 Exposure controls**Appropriate engineering controls**

No data available.

Personal protective equipment**Respiratory protection**

If workplace exposure limits are exceeded, a respiration protection approved for this particular job must be worn. In case of aerosol, vapour and mist formation, take appropriate measures for breathing protection in the event workplace threshold values are not specified. combination filter

Respirator EN14387-A

Eye / face protection

Safety glasses with side protection shield (EN 166)

Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

Appropriate Material In case of short-term contact / splash protection: PVC

Material thickness 0,8 mm

Breakthrough time 4 h

Other

Normal chemical work clothing.

Appropriate Material cotton

Environmental exposure controls

No data available.

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**

State of aggregation
liquid
Form/Colour
liquid
Various, depending on coloration
Odour

**Trade name:** masteroil Diesel Extra-Power**Product no.:** 1606**Current version :** 1.0.2, issued: 21.04.2022**Replaced version:** 1.0.1, issued: 17.01.2022**Region:** IE

No data available

pH value

No data available

Boiling point / boiling range

Value > 160 °C

Melting point/freezing point

No data available

Decomposition temperature

No data available

Flash point

Value > 61 °C

Ignition temperature

No data available

Flammability

No data available

Lower explosion limit

No data available

Upper explosion limit

No data available

Vapour pressure

No data available

Relative vapour density

No data available

Relative density

No data available

Density

No data available

Solubility

No data available

Partition coefficient n-octanol/water (log value)

No	Substance name	CAS no.	EC no.
1	2-ethylhexyl nitrate	27247-96-7	248-363-6
log Pow		5,24	
Method		OECD 117	
Source		ECHA	

Kinematic viscosity

Value	<	20,5	mm ² /s
Reference temperature		40	°C
Type	kinematic		

Particle characteristics

No data available

9.2 Other information**Other information**

No data available.

SECTION 10: Stability and reactivity**10.1 Reactivity**

**Trade name:** masteroil Diesel Extra-Power**Product no.:** 1606**Current version :** 1.0.2, issued: 21.04.2022**Replaced version:** 1.0.1, issued: 17.01.2022**Region:** IE

Dangerous reactions are not expected if the product is handled according to its intended use.

10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

10.3 Possibility of hazardous reactions

Dangerous reactions are not to be expected when handling product according to its intended use.

10.4 Conditions to avoid

Heat, naked flames and other ignition sources.

10.5 Incompatible materials

None known.

10.6 Hazardous decomposition products

No hazardous decomposition products known.

SECTION 11: Toxicological information**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

Acute oral toxicity (result of the ATE calculation for the mixture)	
No	Product Name
1	masteroil Diesel Extra-Power
Comments	The result of the applied calculation method according to the European Regulation (EC) 1272/2008 (CLP), Paragraph 3.1.3.6, Part 3 of Annex I is outside the values that imply a classification / labelling of this mixture according to table 3.1.1 defining the respective categories (ATE oral > 2000 mg/kg).

Acute oral toxicity			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, aromatics (2-30 %)	-	920-360-0
LD50	>	4150	mg/kg bodyweight
Species	rat		
Method	OECD 423		
Source	ECHA		

Acute dermal toxicity (result of the ATE calculation for the mixture)	
No	Product Name
1	masteroil Diesel Extra-Power
Comments	The result of the applied calculation method according to the European Regulation (EC) 1272/2008 (CLP), Paragraph 3.1.3.6, Part 3 of Annex I is outside the values that imply a classification / labelling of this mixture according to table 3.1.1 defining the respective categories (ATE dermal > 2000 mg/kg).

Acute dermal toxicity			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, aromatics (2-30 %)	-	920-360-0
LD50	>	2000	mg/kg bodyweight
Species	rabbit		
Method	OECD 402		
Source	ECHA / Read across		

Acute inhalational toxicity (result of the ATE calculation for the mixture)	
No	Product Name
1	masteroil Diesel Extra-Power

**Trade name:** masteroil Diesel Extra-Power**Product no.:** 1606**Current version :** 1.0.2, issued: 21.04.2022**Replaced version:** 1.0.1, issued: 17.01.2022**Region:** IE

Comments	The result of the applied calculation method according to the European Regulation (EC) 1272/2008 (CLP), Paragraph 3.1.3.6, Part 3 of Annex I is outside the values that imply a classification / labelling of this mixture according to table 3.1.1 defining the respective categories (ATE for inhalation: > 20.000 ppmV (gases), > 20 mg/l (vapours), > 5 mg/l (dusts/mists).
----------	---

Acute inhalational toxicity			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, aromatics (2-30 %)	-	920-360-0
LC50	>	5,28	mg/l
Duration of exposure		4	h
State of aggregation	Vapour		
Species	rat		
Method	OECD 403		
Source	ECHA / Read across		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Skin corrosion/irritation			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, aromatics (2-30 %)	-	920-360-0
Species	rabbit		
Method	OECD 404		
Source	ECHA / Read across		
Evaluation	non-irritant		
Evaluation/classification	Based on available data, the classification criteria are met.		

Serious eye damage/irritation			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, aromatics (2-30 %)	-	920-360-0
Species	rabbit		
Method	OECD 405		
Source	ECHA / Read across		
Evaluation	non-irritant		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Respiratory or skin sensitisation			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, aromatics (2-30 %)	-	920-360-0
Route of exposure	Skin		
Species	guinea pig		
Method	OECD 406		
Source	ECHA / Read across		
Evaluation	non-sensitizing		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Germ cell mutagenicity			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, aromatics (2-30 %)	-	920-360-0
Source	ECHA / Read across		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Reproduction toxicity			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, aromatics (2-30 %)	-	920-360-0

**Trade name:** masteroil Diesel Extra-Power**Product no.:** 1606**Current version :** 1.0.2, issued: 21.04.2022**Replaced version:** 1.0.1, issued: 17.01.2022**Region:** IE

Source	ECHA / Read across
Evaluation/classification	Based on available data, the classification criteria are not met.

Carcinogenicity			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, aromatics (2-30 %)	-	920-360-0

Source	ECHA / Read across
Evaluation/classification	Based on available data, the classification criteria are not met.

STOT - single exposure			
No data available			

STOT - repeated exposure			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, aromatics (2-30 %)	-	920-360-0

Source	ECHA / Read across
Evaluation/classification	Based on available data, the classification criteria are not met.

Aspiration hazard			
No data available			

11.2 Information on other hazards**Endocrine disrupting properties**

No data available.

Other information

No data available.

SECTION 12: Ecological information**12.1 Toxicity**

Toxicity to fish (acute)			
No	Substance name	CAS no.	EC no.
1	2-ethylhexyl nitrate	27247-96-7	248-363-6

LC50		2	mg/l
Duration of exposure		96	h
Species	Danio rerio		
Method	OECD 203		
Source	ECHA		

No	Substance name	CAS no.	EC no.
2	hydrocarbons, C10, aromatics, <1% naphthalene	-	918-811-1
LL50		>= 2	5 mg/l
Duration of exposure		96	h
Species	Oncorhynchus mykiss		
Method	OECD 203		
Source	ECHA		

Toxicity to fish (chronic)			
No data available			

Toxicity to Daphnia (acute)			
No	Substance name	CAS no.	EC no.
1	2-ethylhexyl nitrate	27247-96-7	248-363-6

EC50		>	12,6 mg/l
Duration of exposure		48	h
Species	Daphnia magna		
Method	OECD 202		
Source	ECHA		

No	Substance name	CAS no.	EC no.
2	hydrocarbons, C10, aromatics, <1% naphthalene	-	918-811-1
EL50		>= 3	10 mg/l

**Trade name:** masteroil Diesel Extra-Power**Product no.:** 1606**Current version :** 1.0.2, issued: 21.04.2022**Replaced version:** 1.0.1, issued: 17.01.2022**Region:** IE

Duration of exposure	48	h
Species	Daphnia magna	
Method	OECD 202	
Source	ECHA	

Toxicity to Daphnia (chronic)

No data available

Toxicity to algae (acute)

No	Substance name	CAS no.	EC no.
1	2-ethylhexyl nitrate	27247-96-7	248-363-6
EC50		1,57	mg/l
Duration of exposure		72	h
Species	Pseudokirchneriella subcapitata		
Method	OECD 201		
Source	ECHA		
2	hydrocarbons, C10, aromatics, <1% naphthalene	-	918-811-1
EL50	>= 1	- 3	mg/l
Duration of exposure		72	h
Species	Pseudokirchneriella subcapitata		
Method	OECD 201		
Source	ECHA		

Toxicity to algae (chronic)

No data available

Bacteria toxicity

No data available

12.2 Persistence and degradability

Biodegradability			
No	Substance name	CAS no.	EC no.
1	hydrocarbons, C10, aromatics, <1% naphthalene	-	918-811-1
Type	COD		
Value		49,56	%
Duration		28	day(s)
Method	OECD 301 F		
Source	ECHA		
Evaluation	not readily biodegradable		

12.3 Bioaccumulative potential

Partition coefficient n-octanol/water (log value)			
No	Substance name	CAS no.	EC no.
1	2-ethylhexyl nitrate	27247-96-7	248-363-6
log Pow		5,24	
Method	OECD 117		
Source	ECHA		

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

Results of PBT and vPvB assessment	
PBT assessment	No data available.
vPvB assessment	No data available.

12.6 Endocrine disrupting properties

No data available.

12.7 Other adverse effects

No data available.

**Trade name:** masteroil Diesel Extra-Power**Product no.:** 1606**Current version :** 1.0.2, issued: 21.04.2022**Replaced version:** 1.0.1, issued: 17.01.2022**Region:** IE**12.8 Other information****Other information**

Do not discharge product unmonitored into the environment.

SECTION 13: Disposal considerations**13.1 Waste treatment methods****Product**

Allocation of a waste code number, according to the European Waste Catalogue, should be carried out in agreement with the regional waste disposal company.

Packaging

Residues must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer.

SECTION 14: Transport information**14.1 Transport ADR/RID/ADN**

The product is not subject to ADR/RID/ADN regulations.

14.2 Transport IMDG

The product is not subject to IMDG regulations.

14.3 Transport ICAO-TI / IATA

The product is not subject to ICAO-TI / IATA regulations.

14.4 Other information

No data available.

14.5 Environmental hazards

Information on environmental hazards, if relevant, please see 14.1 - 14.3.

14.6 Special precautions for user

No data available.

14.7 Maritime transport in bulk according to IMO instruments

Not relevant

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulations****Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)**

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

REACH candidate list of substances of very high concern (SVHC) for authorisation

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, MIXTURES AND ARTICLES

The product is considered being subject to REACH regulation (EC) 1907/2006 annex XVII. No 3

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances

This product is not subject to Part 1 or 2 of Annex I.

Trade name: masteroil Diesel Extra-Power

Product no.: 1606

Current version : 1.0.2, issued: 21.04.2022

Replaced version: 1.0.1, issued: 17.01.2022

Region: IE

15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for this mixture.

SECTION 16: Other information

Sources of key data used to compile the data sheet:

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

Directives 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164.

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding section.

Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)

EUH044	Risk of explosion if heated under confinement.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

Creation of the safety data sheet

UMCO GmbH

Georg-Wilhelm-Str. 187, D-21107 Hamburg

Tel.: +49 40 / 555 546 300 Fax: +49 40 / 555 546 357 e-mail: umco@umco.de

This information is based on our present knowledge and experience.

The safety data sheet describes products with a view to safety requirements.

It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO GmbH.

Prod-ID 778311