

Technical Data Sheet masteroil Long-Term Diesel Engine Protection Art-No: 0055301610251

Technical Data

Appearance:Clear yellow-brown liquiddensity (15 °C):0,85 kg/lviscosity (at 20°C):2,98 mm2/sflash point:72,7 °C

Ingredients:

Formulation of various active agents in mineral oil solvent.

Product description:

Additive for diesel fuels, for higher performance and better fuel economy.

Field of Application:

For regular use in diesel engines, to improve operating behaviour and increase performance and service life.

Benefits:

- ✓ Improvement of ignition behavior and starting performance
- ✓ Improvement of cold flow properties
- ✓ Low-noise operation
- ✓ Cleaning of injection nozzles and burning chamber
- ✓ Reduction of exhaust gas emissions
- ✓ Reduction of steel corrosion and wear
- Improvement of thermal and storage stability
- ✓ Prevention of foam formation

Product advantages:

- ✓ Optimises combustion
- ✓ Cleans the fuel system and injectors
- ✓ Ensures a clean engine
- ✓ Improves the longevity of the engine
- ✓ Reduces fuel consumption
- ✓ Increases cold-start reliability of the fuel
- ✓ Suitable for all diesel engines

Telefon +49 231 44424764 masteroil.com info@masteroil.com



Application:

Add the additive to the fuel before or after refuelling. One bottle (250 ml) is enough for up to 60 litres of diesel. The masteroil Long-Term Diesel Engine Protection is intended for routine application and is suitable for all diesel fuels.

Dosage:

From 1:300 (3333 mg/kg) til 1:200 (5000 mg/kg). Recommended dosage rate: 1:200 (5000 mg/kg)

Supply form:

The additive is available in a 250ml can with a pouring spout.

Storage:

Store in a dry place at room temperature, temporarily higher temperatures are unproblematic. Opened containers should be resealed correctly. Avoid storage in direct sunlight. The shelf life of the products is 24 months minimum. Empty containers should be properly disposed.

Safety Considerations:

For detailed handling precautions see masteroil safety data sheet No. 1605

User instructions:

The information and our technical advice are given in good faith according to our best knowledge but without warranty, and this also applies where proprietary rights of third parties are involved.

Telefon +49 231 44424764 masteroil.com info@masteroil.com