



masteroil

# masteroil MULTI ATF

## Description

masteroil MULTI ATF is an HC synthetic high-performance transmission fluid. It was developed to provide extended drainage options. It contains high-grade HC synthetic base oils and advanced additive technology. It is suitable for use in automatic transmissions in both HGVs and buses.

## Application

masteroil MULTI ATF is a multifunctional ATF that combines the requirements set out in the most common specifications laid down by American, European and Japanese manufacturers.

## Typical characteristic values

Property	Method	Unit	Value
Density at 15°C	ASTM D4052	g/ml	0.848
Kinematic viscosity at 40°C	ASTM D445	mm²/s	42.0
Kinematic viscosity at 100°C	ASTM D445	mm²/s	8.4
Viscosity index	ASTM D2270	–	181
Pour point	ASTM D6892	°C	-48
Brookfield viscosity at -40°C	ASTM D2983	mPa-S	18000
Colour	–	Visual	Red

We reserve the right to change our products' general properties so that our customers can always benefit from the latest technical developments.

## Specifications

- Allison C4 / TES 295
- Ford MERCON
- GM DEXRON III-H
- MAN 339 Type V2/Z2 / 399 Z11
- MB 236.9
- Voith H55.6336.xx
- Volvo STD 1273.40 (97340), Volvo STD 1273.41 (97341)
- ZF TE-ML 03 / 04D / 14A / 14B / 14C / 16L / 17C / 20B

## Advantages

Wear protection: Significantly extended transmission service life. Friction properties: Very quiet gear changes without vibrations.

Extended oil life: Excellent temperature and oxidation stability.

## Notes

masteroil MULTI ATF is not suitable for use in DCT / DSG (dual clutch) transmissions or in CVTs (continuously variable transmissions).

## This product is available in the following container sizes:

- 1 litre
- 5 litres
- 30 litres
- 60 litres