

Trade name: masteroil Diesel Extra-Power**Product no.:** 1606**Current version :** 1.0.3, issued: 08.05.2024**Replaced version:** 1.0.2, issued: 21.04.2022**Region:** IE**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifier****Trade name****masteroil Diesel Extra-Power****UFI:****NCV5-C0QP-E006-2F86****1.2 Relevant identified uses of the substance or mixture and uses advised against****Relevant identified uses of the substance or mixture**

Additive for mineral oil products

Uses advised against

No data available.

1.3 Details of the supplier of the safety data sheet**Address**Masteroil GmbH
Stockholmer Allee 30 b
44269 DortmundTelephone no. 0231 444 247 64
e-mail info@masteroil.com**Advice on Safety Data Sheet**

sdb_info@umco.de

1.4 Emergency telephone number

+353 1 809 2166 (National Poisons Information Centre)

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture****Classification in accordance with Regulation (EC) No 1272/2008 (CLP)**

Aquatic Chronic 2; H411

Asp. Tox. 1; H304

Classification information

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

2.2 Label elements**Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)****Hazard pictograms**

GHS08



GHS09

Signal word

Danger

Hazardous component(s) to be indicated on label:

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, aromatics (2-30 %)

**Trade name:** masteroil Diesel Extra-Power**Product no.:** 1606**Current version :** 1.0.3, issued: 08.05.2024**Replaced version:** 1.0.2, issued: 21.04.2022**Region:** IE**Hazard statement(s)**

H304 May be fatal if swallowed and enters airways.
 H411 Toxic to aquatic life with long lasting effects.

Hazard statements (EU)

EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statement(s)

P273 Avoid release to the environment.
 P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.
 P331 Do NOT induce vomiting.
 P391 Collect spillage.

UFI:

NCV5-C0QP-E006-2F86

2.3 Other hazards

PBT assessment
 No data available.

vPvB assessment
 No data available.

SECTION 3: Composition/information on ingredients**3.1 Substances**

Not applicable. The product is not a substance.

3.2 Mixtures**Hazardous ingredients**

No	Substance name		Additional information	
	CAS / EC / Index / REACH no	Classification (EC) 1272/2008 (CLP)	Concentration	%
1	Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)			
	- 925-653-7 - 01-2119458869-15	EUH066 Asp. Tox. 1; H304 Aquatic Chronic 3; H412	>= 25,00 - < 50,00	wt%
2	Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, aromatics (2-30 %)			
	- 920-360-0 - 01-2119448343-41	Asp. Tox. 1; H304 EUH066	>= 25,00 - < 50,00	wt%
3	2-ethylhexyl nitrate			
	27247-96-7 248-363-6 - 01-2119539586-27	Acute Tox. 4; H302 Acute Tox. 4; H312 Acute Tox. 4; H332 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH044 EUH066	< 20,00	wt%
4	hydrocarbons, C10, aromatics, <1% naphthalene			
	- 918-811-1 - 01-2119463583-34	Aquatic Chronic 2; H411 Asp. Tox. 1; H304 EUH066 STOT SE 3; H336	< 2,50	wt%

Full Text for all H-phrases and EUH-phrases: pls. see section 16

SECTION 4: First aid measures

Trade name: masteroil Diesel Extra-Power**Product no.:** 1606**Current version :** 1.0.3, issued: 08.05.2024**Replaced version:** 1.0.2, issued: 21.04.2022**Region:** IE

4.1 Description of first aid measures

General information

Remove contaminated clothing and shoes immediately, and launder thoroughly before reusing. If the patient is likely to become unconscious, place and transport in stable sideways position. In case of persisting adverse effects, consult a physician.

After inhalation

Remove affected person from the immediate area. Ensure supply of fresh air.

After skin contact

In case of contact with skin wash off immediately with soap and water.

After eye contact

Remove contact lenses. Rinse eye thoroughly under running water keeping eyelids wide open and protecting the unaffected eye (at least 10 to 15 minutes). Seek medical assistance.

After ingestion

Do not induce vomiting - aspiration hazard. Rinse the mouth thoroughly with water. Never give anything by mouth to an unconscious person. If individual is drowsy or unconscious, place in recovery position (on left side, with head down).

4.2 Most important symptoms and effects, both acute and delayed

No data available.

4.3 Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray jet; Foam; Carbon dioxide; Extinguishing powder

Unsuitable extinguishing media

High power water jet

5.2 Special hazards arising from the substance or mixture

In the event of fire, the following can be released: Carbon dioxide (CO₂); Carbon dioxide (CO₂); Vapours are heavier than air and may spread near ground to sources of ignition. May travel considerable distance to source of ignition and flash back.

5.3 Advice for firefighters

Use self-contained breathing apparatus. Wear protective clothing. Cool endangered containers with water spray jet. Do not allow run-off from fire fighting to enter drains or water courses.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Refer to protective measures listed in sections 7 and 8. Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. Keep away from ignition sources.

For emergency responders

No data available. Personal protective equipment (PPE) - see Section 8.

6.2 Environmental precautions

Do not discharge into the drains/surface waters/groundwater. Do not discharge into the subsoil/soil.

6.3 Methods and material for containment and cleaning up

Take up with absorbent material (e.g., sand, kieselguhr, universal binder). When collected, handle material as described under the section heading "Disposal considerations".

6.4 Reference to other sections

No data available.

**Trade name:** masteroil Diesel Extra-Power**Product no.:** 1606**Current version :** 1.0.3, issued: 08.05.2024**Replaced version:** 1.0.2, issued: 21.04.2022**Region:** IE

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Provide good ventilation at the work area (local exhaust ventilation, if necessary). If workplace exposure limits are exceeded, respiratory protection approved for this particular job must be worn. Risks inherent to handling the product must be minimised by applying the appropriate protective and preventive measures. Working processes should - so far as possible, according to the state of the art - be designed to rule out bodily contact or the release of hazardous substances.

General protective and hygiene measures

Do not eat, drink or smoke during work time. Keep away from foodstuffs and beverages. Avoid contact with eyes and skin. Remove soiled or soaked clothing immediately. Wash hands before breaks and after work.

Advice on protection against fire and explosion

Keep away from sources of heat and ignition.

7.2 Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions

Keep container tightly closed in a cool, well-ventilated place.

Recommended storage temperature

Value < 50 °C

Requirements for storage rooms and vessels

Containers which are opened must be carefully closed and kept upright to prevent leakage. Keep only in the original container. Protect from heat and direct sunlight.

Incompatible products

Do not store together with: Acids; Alkalies; oxidizing agents

7.3 Specific end use(s)

No data available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

DNEL, DMEL and PNEC values

DNEL values (worker)

No	Substance name			CAS / EC no	
	Route of exposure	Exposure time	Effect	Value	
1	2-ethylhexyl nitrate			27247-96-7 248-363-6	
	dermal	Long term (chronic)	systemic	1	mg/kg/day
	dermal	Long term (chronic)	local	44	µg/cm ²
	inhalative	Long term (chronic)	systemic	0.35	mg/m ³
2	hydrocarbons, C10, aromatics, <1% naphthalene			-	
	dermal	Long term (chronic)	systemic	12,5	mg/kg/day
	inhalative	Long term (chronic)	systemic	151	mg/m ³

DNEL value (consumer)

No	Substance name			CAS / EC no	
	Route of exposure	Exposure time	Effect	Value	
1	2-ethylhexyl nitrate			27247-96-7 248-363-6	
	oral	Long term (chronic)	systemic	25	µg/kg/day
	dermal	Long term (chronic)	systemic	0.52	mg/kg/day
	dermal	Long term (chronic)	local	22	µg/cm ²



Trade name: masteroil Diesel Extra-Power

Product no.: 1606

Current version : 1.0.3, issued: 08.05.2024

Replaced version: 1.0.2, issued: 21.04.2022

Region: IE

	inhalative	Long term (chronic)	systemic	87	µg/m ³
2	hydrocarbons, C10, aromatics, <1% naphthalene			-	
	oral	Long term (chronic)	systemic	7,5	mg/kg/day
	dermal	Long term (chronic)	systemic	7,5	mg/kg/day
	inhalative	Long term (chronic)	systemic	32	mg/m ³

PNEC values

No	Substance name	CAS / EC no
	ecological compartment	Type
		Value
1	2-ethylhexyl nitrate	27247-96-7 248-363-6
	water	fresh water
	water	marine water
	water	fresh water sediment
	water	marine water sediment
	soil	-
	sewage treatment plant	-

8.2 Exposure controls

Appropriate engineering controls

No data available.

Personal protective equipment

Respiratory protection

If workplace exposure limits are exceeded, a respiration protection approved for this particular job must be worn. In case of aerosol, vapour and mist formation, take appropriate measures for breathing protection in the event workplace threshold values are not specified. combination filter

Respirator EN14387-A

Eye / face protection

Safety glasses with side protection shield (EN 166)

Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

Appropriate Material In case of short-term contact / splash protection: PVC

Material thickness 0,8 mm

Breakthrough time 4 h

Other

Normal chemical work clothing.

Appropriate Material cotton

Environmental exposure controls

No data available.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

State of aggregation
liquid
Form
liquid

Trade name: masteroil Diesel Extra-Power

Product no.: 1606

Current version : 1.0.3, issued: 08.05.2024

Replaced version: 1.0.2, issued: 21.04.2022

Region: IE

Colour	
Various, depending on coloration	

Odour	
No data available	

pH value	
No data available	

Boiling point / boiling range	
Value	> 160 °C

Melting point/freezing point	
No data available	

Decomposition temperature	
No data available	

Flash point	
Value	> 61 °C

Ignition temperature	
No data available	

Flammability	
No data available	

Lower explosion limit	
No data available	

Upper explosion limit	
No data available	

Vapour pressure	
No data available	

Relative vapour density	
No data available	

Relative density	
No data available	

Density	
No data available	

Solubility	
No data available	

Partition coefficient n-octanol/water (log value)			
No	Substance name	CAS no.	EC no.
1	2-ethylhexyl nitrate	27247-96-7	248-363-6
log Pow		5,24	
Method		OECD 117	
Source		ECHA	

Kinematic viscosity	
Value	< 20,5 mm ² /s
Reference temperature	40 °C
Type	kinematic

Particle characteristics	
No data available	

9.2 Other information

Other information

Trade name: masteroil Diesel Extra-Power**Product no.:** 1606**Current version :** 1.0.3, issued: 08.05.2024**Replaced version:** 1.0.2, issued: 21.04.2022**Region:** IE

No data available.

SECTION 10: Stability and reactivity**10.1 Reactivity**

Dangerous reactions are not expected if the product is handled according to its intended use.

10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

10.3 Possibility of hazardous reactions

Dangerous reactions are not to be expected when handling product according to its intended use.

10.4 Conditions to avoid

Heat, naked flames and other ignition sources.

10.5 Incompatible materials

None known.

10.6 Hazardous decomposition products

No hazardous decomposition products known.

SECTION 11: Toxicological information**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

Acute oral toxicity (result of the ATE calculation for the mixture)	
No	Product Name
1	masteroil Diesel Extra-Power
Comments	The result of the applied calculation method according to the European Regulation (EC) 1272/2008 (CLP), Paragraph 3.1.3.6, Part 3 of Annex I is outside the values that imply a classification / labelling of this mixture according to table 3.1.1 defining the respective categories (ATE oral > 2000 mg/kg).

Acute oral toxicity			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, aromatics (2-30 %)	-	920-360-0
LD50	>	4150	mg/kg bodyweight
Species	rat		
Method	OECD 423		
Source	ECHA		

Acute dermal toxicity (result of the ATE calculation for the mixture)	
No	Product Name
1	masteroil Diesel Extra-Power
Comments	The result of the applied calculation method according to the European Regulation (EC) 1272/2008 (CLP), Paragraph 3.1.3.6, Part 3 of Annex I is outside the values that imply a classification / labelling of this mixture according to table 3.1.1 defining the respective categories (ATE dermal > 2000 mg/kg).

Acute dermal toxicity			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, aromatics (2-30 %)	-	920-360-0
LD50	>	2000	mg/kg bodyweight
Species	rabbit		
Method	OECD 402		
Source	ECHA / Read across		

**Trade name:** masteroil Diesel Extra-Power**Product no.:** 1606**Current version :** 1.0.3, issued: 08.05.2024**Replaced version:** 1.0.2, issued: 21.04.2022**Region:** IE

Acute inhalational toxicity (result of the ATE calculation for the mixture)	
No	Product Name
1	masteroil Diesel Extra-Power
Comments	The result of the applied calculation method according to the European Regulation (EC) 1272/2008 (CLP), Paragraph 3.1.3.6, Part 3 of Annex I is outside the values that imply a classification / labelling of this mixture according to table 3.1.1 defining the respective categories (ATE for inhalation: > 20.000 ppmV (gases), > 20 mg/l (vapours), > 5 mg/l (dusts/mists)).

Acute inhalational toxicity			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, aromatics (2-30 %)	-	920-360-0
LC50	>	5,28	mg/l
Duration of exposure		4	h
State of aggregation	Vapour		
Species	rat		
Method	OECD 403		
Source	ECHA / Read across		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Skin corrosion/irritation			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, aromatics (2-30 %)	-	920-360-0
Species	rabbit		
Method	OECD 404		
Source	ECHA / Read across		
Evaluation	non-irritant		
Evaluation/classification	Based on available data, the classification criteria are met.		
2	2-ethylhexyl nitrate	27247-96-7	248-363-6
Species	rabbit		
Method	OECD 404		
Source	ECHA		
Evaluation	non-irritant		

Serious eye damage/irritation			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, aromatics (2-30 %)	-	920-360-0
Species	rabbit		
Method	OECD 405		
Source	ECHA / Read across		
Evaluation	non-irritant		
Evaluation/classification	Based on available data, the classification criteria are not met.		
2	2-ethylhexyl nitrate	27247-96-7	248-363-6
Method	OECD 437		
Source	ECHA		
Evaluation	non-irritant		

Respiratory or skin sensitisation			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, aromatics (2-30 %)	-	920-360-0
Route of exposure	Skin		
Species	guinea pig		
Method	OECD 406		
Source	ECHA / Read across		
Evaluation	non-sensitizing		

**Trade name:** masteroil Diesel Extra-Power**Product no.:** 1606**Current version :** 1.0.3, issued: 08.05.2024**Replaced version:** 1.0.2, issued: 21.04.2022**Region:** IE

Evaluation/classification	Based on available data, the classification criteria are not met.		
2	2-ethylhexyl nitrate	27247-96-7	248-363-6
Route of exposure	Skin		
Species	guinea pig		
Method	OECD 406		
Source	ECHA		
Evaluation	non-sensitizing		

Germ cell mutagenicity			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, aromatics (2-30 %)	-	920-360-0
Source	ECHA / Read across		
Evaluation/classification	Based on available data, the classification criteria are not met.		
2	hydrocarbons, C10, aromatics, <1% naphthalene	-	918-811-1
Type of examination	in vitro gene mutation study in bacteria		
Species	S. typhimurium TA 1535, TA 1537, TA 98 and TA 100		
Method	OECD 471		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are met.		

Reproduction toxicity			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, aromatics (2-30 %)	-	920-360-0
Source	ECHA / Read across		
Evaluation/classification	Based on available data, the classification criteria are not met.		
2	2-ethylhexyl nitrate	27247-96-7	248-363-6
Species	rat		
Method	OECD 421		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Carcinogenicity			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, aromatics (2-30 %)	-	920-360-0
Source	ECHA / Read across		
Evaluation/classification	Based on available data, the classification criteria are not met.		

STOT - single exposure
No data available

STOT - repeated exposure			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, aromatics (2-30 %)	-	920-360-0
Source	ECHA / Read across		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Aspiration hazard
No data available

11.2 Information on other hazards**Endocrine disrupting properties**

No data available.

Other information

No data available.

SECTION 12: Ecological information



Trade name: masteroil Diesel Extra-Power

Product no.: 1606

Current version : 1.0.3, issued: 08.05.2024

Replaced version: 1.0.2, issued: 21.04.2022

Region: IE

12.1 Toxicity

Toxicity to fish (acute)			
No	Substance name	CAS no.	EC no.
1	2-ethylhexyl nitrate	27247-96-7	248-363-6
LC50		2	mg/l
Duration of exposure		96	h
Species	Danio rerio		
Source	OECD 203		
2	hydrocarbons, C10, aromatics, <1% naphthalene	-	918-811-1
LL50		>= 2	5 mg/l
Duration of exposure		96	h
Species	Oncorhynchus mykiss		
with reference to	EG 919-284-0		
Method	OECD 203		
Source	ECHA		

Toxicity to fish (chronic)			
No data available			

Toxicity to Daphnia (acute)			
No	Substance name	CAS no.	EC no.
1	2-ethylhexyl nitrate	27247-96-7	248-363-6
EC50		0,83	mg/l
Duration of exposure		48	h
Species	Daphnia magna		
Method	OECD 202		
Source	ECHA		
2	hydrocarbons, C10, aromatics, <1% naphthalene	-	918-811-1
EL50		>= 3	10 mg/l
Duration of exposure		48	h
Species	Daphnia magna		
with reference to	EG 919-284-0		
Method	OECD 202		
Source	ECHA		

Toxicity to Daphnia (chronic)			
No	Substance name	CAS no.	EC no.
1	2-ethylhexyl nitrate	27247-96-7	248-363-6
EC50		0,83	mg/l
Species	Daphnia magna		
Method	OECD 202		
Source	ECHA		
Evaluation/classification	The classification criteria are met based on the available data. (LC50 < 1 mg/l and log Kow >= 4)		

Toxicity to algae (acute)			
No	Substance name	CAS no.	EC no.
1	2-ethylhexyl nitrate	27247-96-7	248-363-6
EC50		>	2,53 mg/l
Duration of exposure		72	h
Species	Desmodesmus subspicatus		
Method	OECD 201		
Source	ECHA		
2	hydrocarbons, C10, aromatics, <1% naphthalene	-	918-811-1
EL50		>= 1	3 mg/l
Duration of exposure		72	h
Species	Pseudokirchneriella subcapitata		
with reference to	EG 919-284-0		
Method	OECD 201		

**Trade name:** masteroil Diesel Extra-Power**Product no.:** 1606**Current version :** 1.0.3, issued: 08.05.2024**Replaced version:** 1.0.2, issued: 21.04.2022**Region:** IE

Source	ECHA
--------	------

Toxicity to algae (chronic)
No data available

Bacteria toxicity
No data available

12.2 Persistence and degradability

Biodegradability			
No	Substance name	CAS no.	EC no.
1	2-ethylhexyl nitrate	27247-96-7	248-363-6
Type		aerobic biodegradation	
Value		0	%
Duration		28	day(s)
Evaluation		not inherently biodegradable	
2	hydrocarbons, C10, aromatics, <1% naphthalene	-	918-811-1
Type		COD	
Value		49,56	%
Duration		28	day(s)
Method		OECD 301 F	
Source		ECHA	
Evaluation		inherently biodegradable	

12.3 Bioaccumulative potential

Partition coefficient n-octanol/water (log value)			
No	Substance name	CAS no.	EC no.
1	2-ethylhexyl nitrate	27247-96-7	248-363-6
log Pow		5,24	
Method		OECD 117	
Source		ECHA	

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

Results of PBT and vPvB assessment	
PBT assessment	No data available.
vPvB assessment	No data available.

12.6 Endocrine disrupting properties

No data available.

12.7 Other adverse effects

No data available.

12.8 Other information

Other information
Do not discharge product unmonitored into the environment.

SECTION 13: Disposal considerations**13.1 Waste treatment methods****Product**

Allocation of a waste code number, according to the European Waste Catalogue, should be carried out in agreement with the regional waste disposal company.

Packaging

Residues must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer.

**Trade name:** masteroil Diesel Extra-Power**Product no.:** 1606**Current version :** 1.0.3, issued: 08.05.2024**Replaced version:** 1.0.2, issued: 21.04.2022**Region:** IE**SECTION 14: Transport information****14.1 UN number or ID number**

ADR/RID/ADN	UN3082
IMDG	UN3082
ICAO-TI / IATA	UN3082

14.2 UN proper shipping name

ADR/RID/ADN	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
Technical name	2-ethylhexyl nitrate hydrocarbons, C10, aromatics, <1% naphthalene

IMDG	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
Technical name	2-ethylhexyl nitrate hydrocarbons, C10, aromatics, <1% naphthalene

ICAO-TI / IATA	Environmentally hazardous substance, liquid, n.o.s.
Technical name	2-ethylhexyl nitrate hydrocarbons, C10, aromatics, <1% naphthalene

14.3 Transport hazard class(es)

ADR/RID/ADN - Class	9
Label	9
Classification code	M6
Tunnel restriction code	-
Hazard identification no.	90

IMDG - Class	9
Label	9

ICAO-TI / IATA - Class	9
Label	9

14.4 Packing group

ADR/RID/ADN	III
IMDG	III
ICAO-TI / IATA	III

14.5 Environmental hazards

ADR/RID/ADN	Symbol "fish and tree"
IMDG	Symbol "fish and tree"
EmS	F-A, S-F
ICAO-TI / IATA	Symbol "fish and tree"

14.6 Special precautions for user

No data available.

14.7 Maritime transport in bulk according to IMO instruments

Not relevant

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulations****Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)**

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

REACH candidate list of substances of very high concern (SVHC) for authorisation



Trade name: masteroil Diesel Extra-Power

Product no.: 1606

Current version : 1.0.3, issued: 08.05.2024

Replaced version: 1.0.2, issued: 21.04.2022

Region: IE

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.
--

Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, MIXTURES AND ARTICLES	
---	--

The product is considered being subject to REACH regulation (EC) 1907/2006 annex XVII.	No 3
--	------

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances	
---	--

This product is subject to Part I of Annex I, risk category:	E2
--	----

15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for this mixture.

SECTION 16: Other information

Sources of key data used to compile the data sheet:

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

Directives 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164.

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding section.

Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)

EUH044	Risk of explosion if heated under confinement.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Creation of the safety data sheet

UMCO GmbH

Georg-Wilhelm-Str. 187, D-21107 Hamburg

Tel.: +49 40 / 555 546 300 Fax: +49 40 / 555 546 357 e-mail: umco@umco.de

This information is based on our present knowledge and experience.

The safety data sheet describes products with a view to safety requirements.

It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

Alterations/supplements:

Alterations to the previous edition are marked in the left-hand margin.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO GmbH.

Prod-ID 778311