



masteroil

## masteroil Hytec e-lixiere SP 0W-30

This is a full synthetic lubricant based on carefully selected very high quality base oils. This oil is specifically formulated to meet both the BMW Longlife-12 FE and the Ford WSS M2C950-A specification. It is adapted to meet the requirements of the latest technology, highly engineered turbo engines requiring high performance and lower viscosity oils.

### APPLICATIONS

This product is mandatory in the newest BMW and Ford gasoline and diesel engines. It provides a multi vehicle application through the ACEA C2 specification. Optimum formulation for today's cars with exceptional film strength preventing oil film breakdown and reducing friction providing fuel economy and reliability.

### FEATURES

Total engine protection: performance in keeping the engine clean. Fuel economy: superior fuel economy and CO2 reduction.

Cold start: excellent fluidity at low temperature.

### PERFORMANCE

ACEA	C2 / A5/B5
API	SN Plus
API	SP
ILSAC	GF-5 / GF-6 A
BMW	LONGLIFE-12 FE
DAIMLER TRUCK	DTFR 15D100
FIAT	9.55535-DS1
FIAT	9.55535-GS1
FORD	WSS-M2C950-A
JAGUAR-LAND-ROVER	STJLR.03.5007
MB	227.61
MB	229.61
OPEL	OV 040 1547 - G30
VW	530 35

### TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.843
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	48.3
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	9.8
Viscosity index	ASTM D2270		194
B.N. (HCLO4 method)	ASTM D2896	mg KOH/g	9.4
Pour point	ASTM D6892	°C	-48
Flash Point COC	ASTM D92	°C	224

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

