



masteroil C-Tec Power 5W-40

Description

Description

masteroil C-Tec Power 5W-40 is a high-performance engine oil based on HC synthetic oil with a wide range of applications. The interaction of the selected base oils and the modern additives results in its high performance level.

Application

masteroil C-Tec Power 5W-40 was specifically developed to meet the needs of modern petrol and diesel vehicles. It is particularly suitable for vehicles with petrol and diesel engines both with and without turbocharging and is used for vehicles that do not have extended maintenance intervals. Its modern concept enables a wide range of applications and ensures safe operation under all operating conditions.

| Typical characteristic values Property | Method | Unit | Value |
|---|------------|--------------------|-------|
| Density at 15°C | ASTM D4052 | g/ml | 0.858 |
| Kinematic viscosity at 40°C | ASTM D445 | mm ² /s | 86.0 |
| Kinematic viscosity at 100°C | ASTM D445 | mm ² /s | 14.4 |
| Viscosity index | ASTM D2270 | – | 175 |
| Base number (HClO ₄ method) | ASTM D2896 | mg KOH/g | 10.5 |
| Pour point | ASTM D6892 | °C | -45 |
| CCS viscosity at -30°C | ASTM D5293 | mPa·S | 6100 |
| Sulphated ash | ASTM D874 | Mass % | 1.27 |
| Flash point (COC) | ASTM D92 | °C | 220 |

We reserve the right to change our products' general properties so that our customers can always benefit from the latest technical developments.

Releases

- MB release 229.3
- VW 502 00 / 505 00

Specifications

- ACEA A3/B3
- API CF / SN
- BMW Longlife-01
- Fiat 9.55535-H2 / 9.55535-M2 / 9.55535-Z2
- MB 226.5
- Opel GM-LL-A-025 / GM-LL-B-025
- Porsche A40
- PSA B71 2296
- Renault RN 0700 / 0710

Advantages

After-treatment protection: All-round protection of the after-treatment system.

Comprehensive engine protection: Excellent cleanliness and engine life.

This product is available in the following container sizes:

- 0.5 litres
- 5 litres
- 60 litres
- 206 litres
- Loose items