



masteroil

masteroil C-Tec Special F 0W-30

Description

masteroil C-Tec Special F 0W-30 is an engine oil specifically developed for modern Ford diesel engines and based on selected HC synthetic base oils. It is suitable for the TDCI Ford Duratorq engines (built from 2014 onwards) and other petrol and diesel engines, and the use of masteroil C-Tec Special F 0W-30 is recommended whenever one of the following specifications is required. The state-of-the-art viscosity index improver ensures high stability and thus long change intervals. The use of biofuels was also taken into account. The lubricant has special elastomer compatibility and offers excellent chain wear protection.

Application

masteroil C-Tec Special F 0W-30 protects the particulate filter due to a reduced sulphated ash content and, at the same time, offers excellent engine protection even at the lowest outdoor temperatures due to its special viscosity level. It is used according to the manufacturer's specifications in vehicles with petrol and diesel engines both with and without a turbocharger and diesel particulate filter.

Typical characteristic values Property	Method	Unit	Value
Density at 15°C	ASTM D4052	g/ml	0.844
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	48.9
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	9.6
Viscosity index	ASTM D2270	-	187
Base number (HClO ₄ method)	ASTM D2896	mg KOH/g	8.0
Pour point	ASTM D6892	°C	-42
Sulphated ash	ASTM D874	Mass %	0.79
Flash point (COC)	ASTM D92	°C	210
CCS viscosity at -35°C	ASTM D5293	mPa-S	5600

We reserve the right to change our products' general properties so that our customers can always benefit from the latest technical developments.

Specifications

- ACEA C2
- Fiat 9.55535-DS1 / -GS1
- Ford WSS-M2C950-A
- Jaguar Land Rover STJLR.03.5007

In addition, this product is recommended when the following filling instructions are required

- Honda
- Jeep
- Mitsubishi
- Subaru
- Suzuki
- Toyota

Advantages

General engine protection: Keeps the engine powerful and clean. Fuel consumption: Low consumption and low CO₂ emissions. Cold start: Excellent flowability at low temperatures.

This product is available in the following container sizes:

- 0.5 litres
- 5 litres
- 30 litres
- 60 litres
- 206 litres
- Loose items

