

masteroil C-Tec Power C6 0W-20

Description

This is an HC synthetic lubricant that is mandatory for the latest engines requiring ACEA C6. It was designed to extend the life of the emission system and keep its efficiency high. It is also designed to provide superior cleanliness, wear protection and long engine life, so your engine will run like new.

Application

This product was specifically developed in view of the challenging requirements set out in the current C6 standard (applicable where ACEA C5 is recommended). A standard where fuel efficiency, low CO² emissions and protection from LSPI are important. It was also developed to meet the latest FORD WWS-M2C952-A specification, which is required for the latest FORD EcoBlue engines (diesel)

Typical characteristic values Property	Method	Unit	Value
Density at 15°C	ASTM D4052	g/ml	0.843
Kinematic viscosity at 40°C	ASTM D445	mm²/s	39.8
Kinematic viscosity at 100°C	ASTM D445	mm²/s	8.3
Viscosity index	ASTM D2270	_	191
Base number (HClO ₄ method)	ASTM D2896	mg KOH/g	9.4
Pour point	ASTM D6892	°C	-45
Flash point (COC)	ASTM D92	°C	234

We reserve the right to change our products' general properties so that our customers can always benefit from the latest technical developments.

Releases

• MB release 229.71

Specifications

- ACEA C5 / C6
- API SN Plus; SP
- Ford WSS-M2C952-A1
- GM DexosD®
- ILSAC GF-6 A
- Jaguar Land Rover STJLR.03.5006
- Opel OV 040 1547 A20

In addition, this product is recommended when the following filling instructions are required

- Acura
- Aston Martin
- Buick
- Cadillac
- Chevrolet
- Chrysler
- Dodge
- Fiat
- GMC
- Honda
- Hyundai
- Infiniti
- Jeep
- Kia
- Lexus
- Lincoln
- Mazda
- MG
- Mitsubishi
- Nissan
- Perodua
- Roewe
- Scion
- Subaru
- Suzuki
- Tata
- Tianjin
- Toyota

Advantages

Wear protection: Considerably reduces wear

Cleanliness: Prevents soot and deposits

Fuel savings: Ensures fuel savings and low CO₂ emissions

This product is available in the following container sizes:

- 0.5 litres
- 5 litres
- 30 litres
- 60 litres
- 206 litres

masteroil GmbH | Stockholmer Allee 30 b | D - 44269 Dortmund| info@masteroil.com