



masteroil C-Tec Special Racing 10W-60

Description

masteroil C-Tec Special Racing 10W-60 is an HC synthetic lubricant based on carefully selected, highly refined base oils. This is a latest-generation engine oil for the lubrication of all petrol and diesel engines with turbochargers in cars.

Application

masteroil C-Tec Special Racing 10W-60 demonstrates very good cold start behaviour and fast oil penetration at the lowest temperatures. At the same time, it provides a stable lubricating film for reliable wear protection even when oil is hot and under extreme loads. masteroil C-Tec Special Racing 10W-60 has been developed to meet the needs of modern petrol and diesel engines. It is mainly used for challenging tasks in the likes of motorsports, or in hot climates. Its high viscosity ensures perfect lubrication under these conditions.

Typical characteristic values

Property	Method	Unit	Value
Density at 15°C	ASTM D4052	g/ml	0.866
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	171
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	24.5
Viscosity index	ASTM D2270	–	175
Base number (HClO ₄ method)	ASTM D2896	mg KOH/g	10.2
Pour point	ASTM D6892	°C	-36
CCS viscosity at -25°C	ASTM D5293	mPa-S	6,700
Sulphated ash	ASTM D874	Mass %	1.1
Flash point (COC)	ASTM D92	°C	238

We reserve the right to change our products' general properties so that our customers can always benefit from the latest technical developments.

Specifications

- ACEA A3/B4
- API SN/CF
- BMW Longlife 01 level
- BMW M models
- MB 229.3 level
- VW 501 01 / 505 00

Advantages

Comprehensive engine protection: Keeps the engine clean

Driving style: Sporty driving.

This product is available in the following container sizes:

- 0.5 litres
- 5 litres
- 30 litres